
SupIR 40mm f/1.0, Fixed Athermalized 680277





HFOV	320x240	384x288	640x480
17µ	7.8°	9.3°	15.3°
12µ	5.5°	6.6°	10.9°

Property			Value	Value			
Optical							
Focal Length			40mm	40mm			
F#			1.0	1.0			
Average transmission (8-12µm)			94% (HD)	94% (HD) / 87% (HC)			
Back Focal Length			17.8mm ir	17.8mm in air			
Mechanical							
Focus Mechanism			Fixed	Fixed			
Depth of Field			100m to ir	100m to infinity			
Focus Range			3m to infir	3m to infinity			
Weight			121gr	121gr			
Max. Dimensions			Ø52mm x	Ø52mm x 38.1mm			
Environmental							
Operation Temperature			-40°C to +	-40°C to +80°C			
Storage Temperature			-50°C to ⊣	-50°C to +85°C			
Sealing			IP 67 front	IP 67 front element only			
Configurations	Weight (gr)	Dimensions	BWD**	Thread	Coating		
680277-001	121	Ø52mm x 38.1mm		M34x1	HD		
680277-002			10.7		HC		
680277-003				M34x0.5	HC		

^{*} The ICD drawing provided here is primarily a representation and may not accurately reflect the product's actual dimensions and specifications. For precise integration specifications contact your local sales representative.

^{**} The BWD value is calculated for a unique detector setup with varying sealing windows in terms of thickness and material. For more details, contact your local sales representative.

