
## SupIR 8.2mm f/1.0, Manual Focus 680092







| HFOV | 320x240 | 384x288 | 640x480 | 1024x768 |
|------|---------|---------|---------|----------|
| 17µ  | 37.7°   | 45.3°   | 77.5°   |          |
| 12µ  | 26.6°   | 31.9°   | 53.5°   | 88.7°    |

| Property                      |             |                  | Value       | Value                           |         |  |  |  |
|-------------------------------|-------------|------------------|-------------|---------------------------------|---------|--|--|--|
| Optical                       |             |                  |             |                                 |         |  |  |  |
| Focal Length                  |             |                  | 8.2mm       | 8.2mm                           |         |  |  |  |
| F#                            |             |                  | 1.0         | 1.0                             |         |  |  |  |
| Average transmission (8-12µm) |             |                  | 92% (HD)    | 92% (HD) / 87% (HC)             |         |  |  |  |
| Back Focal Length             |             |                  | 13.65mm     | 13.65mm in air                  |         |  |  |  |
| Mechanical                    |             |                  |             |                                 |         |  |  |  |
| Focus Mechanism               |             |                  | Manual      | Manual                          |         |  |  |  |
| Depth of Field                |             |                  | 5m to infin | 5m to infinity                  |         |  |  |  |
| Focus Range                   |             |                  | 0.3m to in  | 0.3m to infinity                |         |  |  |  |
| Weight                        |             |                  | see config  | see configurations table below  |         |  |  |  |
| Max. Dimensions               |             |                  | see config  | see configurations table below  |         |  |  |  |
| Environmental                 |             |                  |             |                                 |         |  |  |  |
| Operation Temperature         |             |                  | -20°C to +  | -20°C to +60°C                  |         |  |  |  |
| Storage Temperature           |             |                  | -40°C to +  | -40°C to +70°C                  |         |  |  |  |
| Sealing                       |             |                  | Not sealed  | Not sealed                      |         |  |  |  |
| Configurations                | Weight (gr) | Dimensions       | BWD**       | Thread                          | Coating |  |  |  |
| 680092-001                    | 190         | Ø53.5mm x 41.4mm | 6.29        | 2x Ø3.0, 3x Ø3.8<br>(w/adapter) | HC      |  |  |  |
| 680092-002                    |             |                  | 0.29        |                                 | HD      |  |  |  |
| 680092-003                    | 157         | Ø53.5mm x 40.5mm | 11          | M48x0.5                         | HC      |  |  |  |

<sup>\*</sup> The ICD drawing provided here is primarily a representation and may not accurately reflect the product's actual dimensions and specifications. For precise integration specifications contact your local sales representative.

<sup>\*\*</sup> The BWD value is calculated for a unique detector setup with varying sealing windows in terms of thickness and material. For more details, contact your local sales representative.

